

# RTF300 RTF600

Bidirectional battery inverter from 300kW to 600kW, can be used alone or with solar charge controllers and other accessories for different application scenarios.

## Features

-  AC-DC converter
-  Flexible configuration
-  Touchscreen LCD
-  Paralleling multiple units
-  Support remote control of DG



[图片]

|                    | RTF300    | RTF600    |
|--------------------|-----------|-----------|
| <b>AC(on-grid)</b> |           |           |
| Rated power        | 280kW     | 560kW     |
| Rated voltage      | 400V      | 400V      |
| Rated current      | 404A      | 808A      |
| Voltage range      | 260V-450V | 260V-450V |
| Rated frequency    | 50±10%    | 50±10%    |
| PF                 | ≥0.98     | ≥0.98     |
| THDI               | ≤5%       | ≤5%       |
| Efficiency         | ≥95%      | ≥95%      |

|                       |  |  |
|-----------------------|--|--|
| <b>DC(output)</b>     |  |  |
| Voltage range         | 200Vdc-950Vdc<br>(full above 500V derate below 500V) | 200Vdc-950Vdc<br>(full above 500V derate below 500V) |
| Max output current    | 560A   | 1120A  |
| Output current ripple | ≤1%  | ≤1%  |
| Voltage accuracy      | ≤0.5%  | ≤0.5%  |
| Current accuracy      | ≤1%  | ≤1%  |

|                            |   |   |
|----------------------------|---|---|
| <b>General Information</b> |   |   |
| Nosie emission             | ≤68Db(A)@1m   | ≤68Db(A)@1m   |
| Operating temperature      | -40 °C~+45 °C, full load;<br>45 °C~55 °C, half load | -40 °C~+45 °C, full load;<br>45 °C~55 °C, half load |
| Storage temperature        | -40 °C~85 °C  | -40 °C~85 °C  |
| Relative humidity          | 0~95% non-condensing                                | 0~95% non-condensing                                |
| Maximum altitude           | < 2000m   | < 2000m   |
| Cooling                    | Smart air cooling                                   | Smart air cooling                                   |
| Dimension (W/H/D)          | 1204/1958/853mm                                     | 1204/1958/853mm                                     |
| Weight                     | 245kg   | 350kg   |

|                      |              |              |
|----------------------|--------------|--------------|
| <b>Communication</b> |              |              |
| Display              | Touch screen | Touch screen |
| Communication        | RS485/CAN    | RS485/CAN    |