



Energy Storage Inverter

JBL-HYB-8K-1PL2



Wide DC working voltage range, 2 MPPT design, adapt to multi-angle and multi-orientation PV panels.



Up to 98% conversion efficiency with lower losses; IP66 Waterproof design, indoor& outdoor use.



One machine for multiple purposes: On-grid + Energy storage + Off-grid.



Support remote monitoring, remote upgrade and automatic battery management.



Up to 7 Intelligent working modes, support remote monitoring on mobile/PC.



Support for lithium batteries, but also to specify the brand of battery adaptation communication.



Colorful touch LCD (4.3/7 inch optional)



5-year standard warranty and 10-year extended warranty.

Input DC (PV side)

Max. PV access power	16kW
Max. PV input power	12.8kW
Max. PV input voltage	550V
Nominal input voltage	360V
MPPT working voltage range	80V-500V
Number of independent MPPT/strings per MPPT	2/2
MPPT max. current	2*36A
Start-up voltage	100V

Output/Input AC (Grid side)

Nominal apparent power	8kW
Max. apparent power	8.8kVA
Nominal voltage	220V/230V
Nominal frequency	50Hz/60Hz
Rated current	36.3A/34.7A
Max. current	40A
Power factor	-0.8~+0.8 (adjustable)
THDi	<3%(Nominal Output)
Grid system pattern	L+N+PE
Max. AC current from utility grid	80A

Output AC (Back-up)

Nominal output power	8kVA
Max. output apparent power	8.8kVA
Nominal output voltage	220V/230V
Nominal output frequency	50Hz/60Hz
Output THDV	<3%
Automatic switch time	<10ms

Battery

Battery type	Li-ion/Lead-acid
Battery voltage range	40V-60V
Max. charging/discharging current	180A
Charging strategy for Li-ion battery	Self-adaption to BMS

Efficiency

Max. MPPT efficiency	99.9%
Europe efficiency	97.5%
Max. battery to load efficiency	94.5%

Protection

Anti islanding protection	Yes
Insulation impedance protection	Yes
RCD detection	Yes
PV reverse polarity protection	Yes
Output over voltage protection	Yes
Output over current protection	Yes

General Data

Dimensions(L/W/H)in mm	375/265/413
Weight	23kg
Operation temperature range	-25°C~60°C
Heat dissipation mode	Smart cooling
IP Class	IP 66
Maximum altitude	4000m
Self-Consumption night	<3W
Topology	Transformerless

Features

LCD display	Yes
Communication interface	WiFi/4G/USB/CAN/RS485

Standards	IEC 62109-1/IEC 62109-2/EN IEC 61000-6-1/EN IEC 61000-6-3/CEI 0-27 VDE AR 4105/VDE V 0124-100/NC RfG/PSE/PTPIREE/EN50549/NRS 097
-----------	---