



NEW



Grid-Tied Inverters

S6-GR3P(3-10)K02-NV-ND

2 MPPT | 21A per MPPT

- String current up to 21A
- Nighttime PID recovery function (optional)
- > 200% DC/AC ratio
- IP66, C5 Anti-Corrosion Level
- Dual independent RS485 ports, supporting communication with multiple devices
- Information scrolling display, easy access to inverter operation information
- 24-hour load consumption monitoring
- Adaptive weak grid

GINLONG TECHNOLOGIES CO., LTD.

t: +86 574 6580 2188 e: sales@ginlong.com
w: solisinverters.com service@ginlong.com



DATASHEET

S6-GR3P(3-10)K02-NV-ND

Models	3K	4K	5K	6K	8K	9K	10K
Input DC							
Recommended max. PV power	4.5 kW	6 kW	7.5 kW	9 kW	12 kW	13.5 kW	15 kW
Max. input voltage	1100 V						
Rated voltage	600 V						
Start-up voltage	160 V						
MPPT voltage range	160 - 1000 V						
Max. input current	21 A / 21 A						
Max. short circuit current	26.5 A / 26.5 A						
MPPT number / Max. input strings number	2 / 2						
Output AC							
Rated output power	3 kW	4 kW	5 kW	6 kW	8 kW	9 kW	10 kW
Max. apparent output power	3 kVA	4 kVA	5 kVA	6 kVA	8 kVA	9 kVA	10 kVA
Max. output power	3 kW	4 kW	5 kW	6 kW	8 kW	9 kW	10 kW
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	4.6 A / 4.3 A	6.1 A / 5.8 A	7.6 A / 7.2 A	9.1 A / 8.7 A	12.2 A / 11.5 A	13.7 A / 13.0 A	15.2 A / 14.4 A
Max. output current	4.6 A / 4.3 A	6.1 A / 5.8 A	7.6 A / 7.2 A	9.1 A / 8.7 A	12.2 A / 11.5 A	13.7 A / 13.0 A	15.2 A / 14.4 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)						
THDi	< 3%						
Efficiency							
Max. efficiency	98.3%				98.5%		
EU efficiency	97.7%				97.9%		
Protection							
DC reverse-polarity protection	Yes						
Short circuit protection	Yes						
Output over current protection	Yes						
Surge protection	Yes						
Grid monitoring	Yes						
Anti-islanding protection	Yes						
Temperature protection	Yes						
I/V Curve scanning	Yes						
Multi peak scan	Yes						
Integrated AFCI 2.0	Optional						
Integrated PID recovery	Optional						
Integrated DC switch	Yes						
General Data							
Dimensions (W × H × D)	355 × 410 × 179 mm						
Weight	14.7 kg				15.4 kg		
Topology	Transformerless						
Self-consumption (night)	< 1 W						
Operating ambient temperature range	-25 ~ +60°C						
Relative humidity	0 - 100%						
Ingress protection	IP66						
Noise emission (typical)	< 30 dB(A)						
Cooling concept	Natural cooling						
Max. operation altitude	4000 m						
Grid connection standard	G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530						
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4						
Features							
DC connection	MC4 connector						
AC connection	Quick connection plug						
Display	LED digital display & Bluetooth + APP						
Communication	RS485, Optional: Wi-Fi, GPRS						